




EcoLine (wersja ekonomiczna)

Płytki pełnowęglkowe, frezarskie ISO APKT1003..., APKT1604...

oferta ważna do 30.09.2023

plytka	gatunek	przeznaczenie	cena [PLN]
APKT 100304PDER-MG FP32HS		● ○ ○	12,35 -
APKT 100308PDER-MG FP32HS		● ○ ○	12,35 -
APKT 100308PDER-MG FP33TX		● ○ ○ ○ ○	14,95 -
APKT 100304PDER-MG FM43TX		○ ● ○ ○	14,95 -
APKT 100308PDER-MG FM43TX		○ ● ○ ○	14,95 -
APKT 100304PDER-AL FK10		○ ●	14,45 -
APKT 160408PDER-MG FP32HS		● ○ ○	15,20 -
APKT 160408PDER-RG FP32HS		● ○ ● ●	15,20 -
APKT 160408PDER-RG FP33TX		● ○ ● ○ ●	18,10 -
APKT 160408PDER-MG FM43TX		○ ● ○ ○	18,10 -
APET 160404PDFR-AL FK10		○ ●	22,35 -



APKT 160404PDER-AL FK10

parametry skrawania:

rodzaje materiałów obrabianych	Vc [m/min]	fz [mm/z]	ap [mm] 10/16
stal (85 - 225 HB)	120 - 250	0.10 - 0.22	0.3 - 7.0 / 11.0
stal nierdzewna	100 - 180	0.08 - 0.18	0.3 - 4.0 / 6.5
żeliwo szare (140 - 220 HB)	120 - 250	0.10 - 0.22	0.3 - 6.0 / 9.5
żaroodporne, stopy tytanu	40 - 100	0.07 - 0.14	0.3 - 4.0 / 6.5
ulepszane cieplnie do 52 HRC	50 - 100	0.07 - 0.15	0.3 - 4.0 / 6.5
nieżelazne, tworzywa, syntetyki	200 - 700	0.10 - 0.40	0.3 - 7.0 / 11.0

